

ELECTROMAGNETIC LOCK DOUBLE DOOR



FEATURES


- + Holding force 560Kg/ 600lbs
- + Lock signal relay NO/NC/COM
- + Door signal NO/NOC/COM
- + Timer 3, 6, 9 seconds
- + LED indicator
- + Anodized aluminum housing
- + Dual operating voltage 12V/24V(optional)
- + No residual magnetism
- + Surge protection using Metal Oxide Varistor
- + Detachable faceplate
- + Complete mounting hardware package
- + L, Z, U, I brackets for easy mounting

SPECIFICATIONS

MATERIAL	
Holding force	560Kg/1200lbs
Housing Material	Anodized aluminum housing
METRICS	
Dimensions LWH (mm)	Size 500 x 48.8 x 27.9
	Armature plate 180 x 38.8 x 13.2
ELECTRICAL	
Input voltage	DC12V/ DC24V (optional)
Consumption	12V/1.0A ±10% (24V/0.5A ±10%)
CERTIFICATIONS	
	CE, FCC, RoHS, WEEE

GENERAL	
Lock signal	NO/ NC/ COM
Door signal	NO/ NC/ COM
LED	Yes (Red-Lock, Green-Unlock)
Timer	Yes (3, 6, 9 seconds)
MTCF	>3 million operations
Ingress protection	IP 54
Storage temperature	-20° C ~ +65° C
Operating temperature	-20° C ~ +65° C
Surface temperature	<21° C
Humidity	90% RH
Weight	4200 grams/ 4.2Kg

DIMENSIONS



BRACKETS (optional)

- L/L2 bracket for outward direction doors
- LZ/LZ2 bracket for inward direction doors
- U/U2 bracket for frameless glass doors
- I/I2 bracket for armature plate for thick door frames

ORDERING METHOD

NU 8285 ERTX Double door electromagnetic lock, 560Kg/1200lbs, IP 54 rated, anodized aluminum housing, LED indicator (green/red), relay for lock NO/NC/CO, timer (3,6,9 seconds), door signal, 12V/24V(optional)

Nundnet, the Nundnet logo, and other trademarks associated with Nundnet products referred to in this publication are trademarks of Nundlab, Inc. USA or its affiliates. The product is warranted for the period of five years under limited conditions. For warranty terms & conditions kindly visit nundnet.com/warranty. Product specifications and availability are subject to change without notice. © Copyright 2014, Nundlab, Inc. USA, All rights reserved.

