

Integrated Access Control Systems & Solutions

Nundnet

ADHESIVE LABEL

FEATURES


Compatible with 860 ~960 MHz
 ISO18000-6C (EPC Class1 Gen2)
 IP X5 rated for outdoor application

GENERAL APPLICATION

Make payments,
 Access control,
 Unlock & control mobile devices,
 Transfer information,
 Link people,
 Special access for VIP Staff,
 Staff management
 etc.



APPLICATIONS



car parking & vehicle access control



ID access control for offices & private buildings



Handfree operation



Retail & property management

SPECIFICATIONS

Frequency Compliance	860 ~960 MHz ISO 18000 - 6C EPC Class 1 Gen 2
Chip	NXP/ Philips/ Nundlab
Memory	96 bit EPC Number
Operation	Read / Write
Read (distance)	1 ~ 12 M
Write (distance)	1 ~ 2 M
Data retention	10 Years (3650 days)
Housing Material	Poly Vinyl Chloride
Antenna material	Copper
Temperature	Operation 25°C ~ 80°C
Ingress Protection	Storage 20°C ~ 50°C
Operation Humidity	80%
Mounting	Wall, Surface
Weight	.002 G
Certification	FCC, NCC, CE, RoHS

Type	Transparent	Silver	Transparent	Silver
Dimension(mm)	105 x 6.5	96 x 22	97 x 15mm	95 x 21mm
Range (M)	12	10 M	9 M	9 ~ 12 M

ORDERING METHOD

NT 10 AHS UHF RFID Adhesive Transparent Tag

NT 10AHS

Nundnet UHF RFID Sticker

Nundnet, the Nundnet logo, and other trademarks associated with Nundnet products referred to in this publication are trademarks of Nundlab, Inc. USA or its affiliates. Product specifications and availability are subject to change without notice. ©Copyright 2017, Nundlab, Inc. USA, All rights reserved.

